

| Base Enclosure | Continuous or Discrete | Gear Train | Special Options | Enclosure Options | Wiring | Thermal Management | PCB | Mounting Kit | Valve Part Number | | | |
|----------------|------------------------|--|-----------------|-------------------|----------|---|--|--------------|-------------------|----------|---|--|
| M | C | M | - | - | 0 | 5 | 0 | AB | - | 1 | - | |
| | | | | | | | | | | | | 0 No Valve or Mounting Kit 1 Mounting Kit, Customer Supplies Valve but Does Not Send Valve to Hanbay 2 Mounting Kit, Customer Supplied Valve Sent to Hanbay 3 Mounting Kit, Hanbay Provides Valve |
| | | | | | | | AB Analog Signal Board AI Analog Signal Board Isolated Input AF Analog Signal Board Isolated with Feedback DC Continuous TTL Input Board DT TTL Input Board with Integrated Feedback AS Modbus Control with Feedback | | | | | |
| M | M-Series | | | | | | | | | | | |
| | C D | Continuous Discrete | | | | | 0 No Option H Internal Heater F External Fan | | | | | |
| | | J Extra Low Torque K M gear train with low torque motor L Low Torque M Medium Torque H High Torque (Additional Gear Stage) F F-Gear Stage (with MCL or MCM) | | | | 0 Cable Gland (Specify Cable and length at additional cost) 4 Custom Dual Guage Cable, 10ft. 5 TURCK 5 Position Connector w. 20' Cable and Plug 6 TURCK 6 Position Connector w. 20' Cable and Plug 7 TURCK 5 Position Connector Only 8 TURCK 8 Position Connector w. 20' Cable and Plug (Special Applications) | | | | | | |
| | | | | | | | 0 Standard Red Alloy Enclosure M Manual Override S Stainless Steel Enclosure N Black Alloy Enclosure | | | | | |
| | | | | | | | 0 No Special Options HT High Temperature Kit B Battery Backup G G-Stage Gate Valve (MCM or MCL) L1 Linear 16 TPI L2 Linear 8 TPI M Manual Override (When M in Enclosure Option is not usable) AC 110VAC Power Supply TS Top Stop BS Bottom Stop | | | | | |

